



Hi-Speed USB 2.0 VGA Converter

Supports up to 6 additional displays

Easily connect an LCD projector or another monitor or SVGA device to notebook or desktop computers.

The MANHATTAN® Hi-Speed USB 2.0 VGA Converter helps increase productivity, improve "desktop" arrangements and extend the visual work area across dual monitors. It helps make word processing, editing and multi-tasking more effective with less-overlapped windows, fewer hidden palettes and better-organized views. Users can read email on one monitor and open attachments on the other. Large, complicated spreadsheets can be expanded and viewed without scrolling. Presentations are made more compelling with another monitor for more impact or viewing speaker notes on a separate display. The MANHATTAN Hi-Speed USB 2.0 VGA Converter supports resolutions of up to 1900 x 1200 in 16-bit or 1600 x 1200 in 32-bit color, and its 16 MB SDRAM memory easily enhances the workspace without complicated installations or expensive equipment.

Easy to Install

The convenient Hi-Speed USB 2.0 connection eliminates the need to install another graphics card or struggle with compatibility issues. It's an ideal portable solution for notebook computers and desktop systems with graphics cards that lack additional outputs. With Plug and Play and hot-swap capabilities, it's easily installed without an external power supply on any Windows computer.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.









Features

- Easily adds a monitor to a computer to expand visual areas
- Software manages up to 6 converters easily add up to 6 displays to a single PC
- Ideal for notebook computers and graphics cards without additional outputs
- Primary, extended and mirror functions provide display continuity and dual views
- Supports resolutions up to 2048 x 1280 in 16-bit or 1680 x 1050 in 32-bit color
- Portable and connects to any USB port without conflicts or external power supplies
- Plug and Play; Windows compatible
- Lifetime Warranty

Specifications

STANDARDS & CERTIFICATIONS

- Hi-Speed USB 2.0
- EHĆI
- CE • FCC

GENERAL

- Chipset: SiS
- Display memory: 16 MB SDRAM
- Bus powered
- Connections: USB type A male; HD 15 female
- Supports Suspend and Wake modes

SUPPORTED RESOLUTIONS

• Wide screen: 16:10; 2048 × 1280; 16 bits 16:10; 1920 × 1200; 16 bits 16:9; 1920 × 1080; 16 bits 16:10; 1680 x 1050; 16/32 bits 16:10; 1440 x 900; 16/32 bits 16:10; 1280 x 800; 16/32 bits 15:9; 1280 x 768; 16/32 bits

- Standard monitor:
- 5:4; 1280 x 1024; 16/32 bits
- 4:3; 1600 x 1200; 16/32 bits 4:3; 1280 x 960; 16/32 bits
- 4:3; 1152 x 864; 16/32 bits
- 4:3; 1024 x 768; 16/32 bits 4:3; 800 x 600; 16/32 bits
- PHYSICAL
- Dimensions: 10.75 x 5 x 2.5 cm (4.25 x 2 x 1 in.)

 Cable length: 45.75 cm (18 in.)

 Weight: 113 g (4 oz.)

 Case material: ABS plastic

SYSTEM REQUIREMENTS

- Windows 2000/XP/Vista/7 compatibleAvailable Hi-Speed USB 2.0 port

PACKAGE CONTENTS

- Hi-Speed USB 2.0 VGA Adapter
- Quick install guide and driver CD

For more information on MANHATTAN products, consult your local dealer or visit **www.manhattan-products.com**.



Copyright @ MANHATTAN