

Glancetron GT19plus

Professional high-end monitors with elegant design



- 48.3 cm (19") touch screen – Flagship of the GTplus series of professional high-end monitors
- Integrated touch screen with resistive touch technology
- Extremely elegant design and especially robust construction
- Dual: touch screen interface with RS232/USB and AC/DC voltage supply
- Maximum resolution: 1,280 x 1,024 pixels

Specifications

General	Model	GT-19 plus
	Colour	Dark Grey
	Dimensions	405.5 x 438 x 267.4 mm (H x W x D)
	Net Weight / Shipping Weight	9.9 kg / 12 kg
	Power Supply	AC Input 90 ~ 264 V / DC 12 V
	Power Consumption	Operating: 25W (typ.) / Sleep: 4W / Off: 2W
Display	Mounting Option	Stand / 100 x 100 mm VESA Mount
	LCD Size / Type	19 Inch TFT Active Matrix Panel
	Active Area	376 x 301 mm (H x V)
	Pixel Pitch	0.297 x 0.297 mm (H x V)
	Panel Resolution	1,280 x 1,024 Pixels
	Display Mode	VGA 720 x 400 (70Hz)
	Display Colour	16.7 Million Colour
	Contrast	800:1
	Brightness	Without Touch 300 nits / SAW 270 nits / Capacitive 255 nits / Resistive 240 nits
	Response Time	Tr: 2 ms / Tf: 6 ms
	Viewing Angle	Horizontal: 80° ~ -80° / Vertical: 80° ~ -80°
	Video Input Format	RGB Analog 0.7 Peak to Peak
	Video Sync Format	Separated H&V Sync. / Composite Sync. / Sync-on Green
	Video Input Frequency	Horizontal: 31Khz ~ 81 kHz / Vertical: 56 Hz ~ 76 Hz
Video Signal Input	D.sub 15 pin Female (Analog)	
Environment	Temperature - Operating	0°C ~ +40°C
	Temperature - Storage	-20°C ~ +60°C
	Control Key	Power On/Off, Select, Down, Up, Menu
	Audio	1W Speaker / 2 Channels



Your Dealer