# VS1804T / VS1808T



### 4/8-Port HDMI Over Cat 5 Splitter

The ATEN VS1804T / VS1808T HDMI Over Cat 5 Splitter is the quickest and most efficient way to move HDMI multimedia content and HDCP information from input source to 4/8 displays.

A one-to-many, point-to-multipoint system for transmission of high definition video and audio, the VS1804T / VS1808T transmits rich multimedia content in real time from HDMI source devices to HDMI display devices over Cat 5e cables. The VS1804T / VS1808T can support multi-displays when combined in an installation with ATEN's HDMI extender\*.

The VS1804T / VS1808T provides the flexibility you need for a customized digital signage or HDMI display installation, allowing you to set up your display device 60 m (200 ft) from the HDMI source devices.

The VS1804T / VS1808T solution is ideal for any installation that requires HDMI content to be delivered to multiple destinations, such as:

Setup

- In-store or tradeshow digital signage
- · Broadcasting information to public locations (news, airline and train schedule and arrival/departure information)
- Sporting events
- Theater and lecture overview rooms
- Classroom and company training facilities

Note\*: Compatible receiving device is VE800R











## Specifications - - - -

VS1808T Rear (child)

VS1808T Rear (parent)

Function			VS1804T	VS1808T
	HDMI In		1 x HDMI Type A Female (Black)	
Connectors	HDMI Out	Local	1 x HDMI Type A Female (Black)	
	Line Out (Cat 5)	TMDS	4 x RJ-45 Female	8 x RJ-45 Female
		DDC	4 x RJ-45 Female	8 x RJ-45 Female
	RS-232		1 x DB-9 Female (Black)	
	Power		1 x DC Jack	
Switches	EDID Mode		1 x 8-Position Switch	
	EDID Learn Mode		1 x Pushbutton	
LEDs	Power		1 (Green)	
	HDMI In		1 (Green)	
	HDMI Out		1 (Green)	
	EDID Learn		1 (Green / Red)	
	Line Out		4 (Green)	8 (Green)
Video		1080p @ 40m; 1080i @ 60m		
Power Consumption		DC5.3V, 8W	DC5.3V, 13W	
Environment	Operating Temp.		0-50°C	
	Storage Temp.		-20–60°C	
	Humidity		0–80% RH, Non-condensing	
Physical Properties	Housing		Metal	
	Weight		2.10 kg	2.15 kg
	Dimensions (L x W x H)		43.24 x 15.41 x 4.40 cm	

HDMI In

HDMI

HDMI Out

#### \* Product specifications and appearance are subject to change without notice.

### Features -----

- One HDMI input to 4/8 HDMI outputs via Cat 5e cables
- Extends displays up to 60 m
- Supports HDMI (3D, Deep color)
- Offers local HDMI output
- HDCP compatible
- Consumer Electronics Control (CEC) allows interconnected HDMI devices to communicate and respond to one remote control
- Cascadable to three levels
- Supports superior video quality HDTV resolutions of 480p, 720p, 1080i and 1080p (1920 x 1080)
- EDID mode selection
- · Rack-mountable

