

Product Specifications

3.5" 40-pin IDE to 1 PCMCIA PC card Card-Drive

R313XX00150XBX03R

Features :

- ❖ Standard 3.5" drive form-factor
- ❖ 1 front PCMCIA type III slot
- ❖ ATA to standard 40-pin IDE interface
- ❖ 40-pin IDE connector and a 4-pin power connector
- ❖ Bootable device
- ❖ Supports PIO-mode only
- ❖ RoHS compliant



Specifications :

❖ Form-factor		Standard 3.5" drive mounted in the front of PC casing
	Dimension	152mm (L) * 101.6mm (W) * 25.4mm (H)
	Weight	G. W.: 260g
❖ Host Interface		40-pin IDE connector and a 4-pin power connector
❖ Slot Capabilities		1 front slot in PCMCIA type III
❖ Master/Slave Setting		By jumper
❖ Supported Card Type		ATA flash card, ATA HDD, and CompactFlash card w/ PC card adapter
❖ Power Consumption		5V/70mA typ.
❖ Environmental Specification		
	Operating Temperature	0°C ~ 70°C
	Non-operating Temperature	-20°C ~ 80°C
	Relative Humidity	Max 90%
❖ Bootable Function		Yes and no driver needed
❖ Data Access		PIO mode only
❖ Supported OS		Any OS workable per IDE interface
❖ Warranty		1 year

Part Number List

R313XX00150XBX03R	40-pin IDE 3.5" card drive with 1 front PCMCIA type III

INDUSTRIAL CompactFlash Card

INDUSTRIAL PCMCIA ATA Card

INDUSTRIAL micro IDE Flash Disk

INDUSTRIAL micro SATA Flash Disk

INDUSTRIAL Solid State Disk

INDUSTRIAL Rugged Metal USB Flash Disk

INDUSTRIAL Adapter Card Reader