

3.5" 40-pin IDE to 1 CF card Card-Drive

R312XX00150XBH03R



Features :

- ❖ Standard 3.5" drive form-factor
- ❖ 1 front CompactFlash type II slot
- ❖ ATA to standard 40-pin IDE interface
- ❖ 40-pin IDE connector and a 4-pin power Connector
- ❖ Hot swappable & bootable
- ❖ Supports up to UDMA-4 mode
- ❖ RoHS compliant

Specifications :

❖ Form-factor		Standard 3.5" drive mounted in the front of PC casing
	Dimension	109.4mm (L) * 101.6mm (W) * 25.4mm (H)
	Weight	G. W.: 270g
❖ Host Interface		40-pin IDE connector and a 4-pin power connector
❖ Slot Capabilities		1 front slot in CompactFlash type II
❖ Master/Slave Setting		By jumper
❖ Supported Card Type		CompactFlash type I/II and MicroDrive
❖ Power Consumption		5V/70mA typ.
❖ Environmental Specification		
	Operating Temperature	0°C ~ 70°C
	Non-operating Temperature	-20°C ~ 80°C
	Relative Humidity	Max 90%
❖ Hot Swap Function		Yes and software supports DOS, Windows 98/ME/2000 /XP; No driver needed for Linux
❖ Bootable Function		Yes and no driver needed
❖ Data Access		PIO mode and DMA mode (up to UDMA-4 mode)
❖ Supported OS		Any OS workable per IDE interface
❖ Warranty		1 year

Part Number List

R312XX00150XBH03R	40-pin IDE 3.5"card drive with 1 front CompactFlash type II

INDUSTRIAL
CompactFlash Card

INDUSTRIAL
PCMCIA ATA Card

INDUSTRIAL
micro IDE Flash Disk

INDUSTRIAL
micro SATA Flash Disk

INDUSTRIAL
Solid State Disk

INDUSTRIAL
USB Flash Disk

INDUSTRIAL
Card Reader