

MimioVote



SPECIFICATIONS

Minimum System Requirements

Software

Installation

Range

Response Time Discrimination

User Input

Max Number of Devices per System

Batteries

Battery Life

Communication

Radio Frequency (RF)

Power Consumption

Dimensions

Weight

DESCRIPTION

The MimioVote™ assessment system makes student assessment fast, flexible, and easy. Create tests with custom or standardized content, and get results in real time, whenever you like. Lead tests yourself, or let students pace themselves. The software automatically configures the clicker buttons students need for each test, and the handheld devices automatically renumber themselves when returned to their recharging tray. The MimioHub™ wireless receiver integrates automatically with the MimioVote system, allowing it to send data instantly to your computer.

PACKAGE CONTENTS

24 or 32 MimioVote rechargeable handheld devices, packed in a durable storage case, with foam-padded compartments, removable docking and charging station, 1 DVD containing MimioStudio software, 1 MimioHub wireless receiver, 1 power supply and cable.

Windows XP, Vista, and Windows 7

Mac OS 10.4

Linux: Fedora, openSUSE, and Ubuntu

For specific system requirements please visit us at: mimio.dymo.com/support/downloads

MimioStudio 7 and higher.

Operation and use of MimioVote devices require MimioStudio 7 software and MimioHub.

9 m (30 ft)

As low as 1 millisecond.

8 response and 2 forward/backward buttons, 1 Help button.

Combine two trays of 32, up to 64 units per classroom.

1 rechargeable Lithium-Ion battery per handheld device.

Fully rechargeable; typically 3 years.

Wireless with the MimioHub, which inserts into computer USB port.

2.4 GHz

5 V 3.0 Amps via EIAJ-2 (1.7mm ID, 4mm OD)

Handheld: 25 mm x 90 mm x 61 mm (1 in. x 3.54 in. x 2.4 in.). Charging Tray: 548 mm x 92 mm x 241 mm (21.6 in. x 3.6 in. x 9.5 in.). Case: 674 mm x 251 mm x 167.64 mm (26.5 in. x 9.8 in. x 6.6 in.).

Handhelds and Tray: 5.2 kg (11.5 lb).

Handhelds, tray, carrying case: 8.4 kg (18.5 lb).



MimioVote

SPECIFICATIONS

Operating Temperatures Storage Temperatures

Question/Answer Types

Question Data Import

Question Preparation

Response Monitoring

Response Modes

Gradebook

LCD screen

Device Numbering

PowerPoint Support

Changing Button Color

Adding handhelds

Certification & Compliance

Warranty and Support

0°C to 50°C (32°F to 122°F). Limited by LCD display. -10°C to 60°C (14°F to 140°F). Limited by LCD display. Operating Humidity: 15% to 75% non-condensing. Storage Humidity: 0% to 90% non-condensing.

Multiple Choice, Yes/No, True/False, Chime In, Question.

ExamView importer (Blackboard 6.0 – 7.0 format).

Notebook allows for question preparation with correct answers.

Questions can be timed.

Results can appear instantly, or be viewed at a later time.

Users can be allowed to modify their response.

Operates in teacher-managed or student-managed modes.

Create a class; add students; import, export and archive student lists; assign

a MimioVote student ID.

Displays device number when stored in tray.

Allows students to navigate backward and forward to display question number

and student response during self-paced assessment.

Devices are automatically numbered when returned to the charging tray.

Numbered devices can be assigned to a user's name through the Gradebook.

Results can be captured by assigned user number or anonymously.

Create questions, polling, present results.

Ability to turn on/off button colors or change individual button colors within tool bar.

Automatic numbering upon insertion into tray.

Wireless: FCC, IC, CE, C-Tick, COFETEL, SCRF, SRMC, TELEC, RRL, TRA, ANRT, ANATEL, WPC, DGPT, CTI, MIC, SIRIM, MOC, CNC, SUBTEL, CRT, SUTEL, BURTEL, CONATEL, SIGET, SIT, PUC, TELCOR, ERSP, OSIPTEL, TATT, URSEC, UrkSEPRO,

ICASA, NTRA, CITC, NCC.

Safety: UL/CSA/EN/IEC 60950-1 (CE &TUV NRTL) C-Tick, NOM, KCC, GOST, ANA-

TEL, SII, UrkSEPRO, NRCS, VoC, CQC.

EMC: FCC, IC, CE, C-Tick, GOST, KCC, ANATEL, SII. Environmental: RoHS, WEEE, REACH compliant.

Mimio hardware is warranted for 2 years from date of purchase, with an additional 3 years with product registration at mimio.dymo.com/warranty, for a total of 5 years. MimioStudio software is supplied with a limited lifetime warranty, expiring 1 year after discontinuation of the product. The rechargeable batteries provided with MimioVote handsets are under warranty for a period of 2 years from the date of purchase. A replacement pack is available for purchase.