



- NOTES
1. ALL DIMENSION ARE IN MILLIMETERS.
  - ② TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN, GLASS IS BEVELED UNDER THE TRANSDUCERS.
  - ③ CABLE ROUTING ADDS A MAXIMUM OF 4.0mm TO INDICATED SECTION OF SCREEN.
  - ④ 8X19 HOUSING MATES WITH CONTROLLER.
  - ⑤ REFLECTONAL ARRAY AND ② TRANSDUCER ON THE FRONT OF THE GLASS.
  - ⑥ CABLE CLIP, MATERIAL: METAL.
  - ⑦ GLASS BOARD.
  - ⑧ CABLE, OUTER LAYER MATERIAL: PVCBG01.
  - ⑨ THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

CONNECTION CHART

PIN	SIGNAL	INSUTLATION COLOR OVERALL SHIELD
1	GND	
2	KEY	
3	Y-in2	BLUE
4	Yout	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	Xout	RED
11	X-in1	RED
12	KEY	