



CONNECTION CHART		
PIN	SIGNAL	INSULATION COLOR OVERALL SHEILD
1	GND	
2	KEY	
3	Y-in2	BLUE
4	Y-out	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	X-out	RED
11	X-in1	RED
12	KEY	

NOTE:
 1. ALL DIMENSIONS ARE IN MILLIMETERS.
 2. THE UNSPECIFIED DIMENSION TOLERANCES ARE PLUS/MINUS 1.
 3. ACTIVE AREA DIMENSIONS: F710 (× 296 W)
 4. VIEWABLE AREA DIMENSIONS: F711 (× 296 W)
 5. PROFILE DIMENSIONS: F53 (S) (× 346.5 W) (× 4.2 D),
 6. SPECIFICATION
 7. ① DUST-PROOF FRAME MATERIAL: ALUMINUM.
 8. ② 8 × 19 HOUSING MATES WITH CONTROLLER
 9. HOUSING MATERIAL: PETUL94Y-40BL-ACX
 10. HOUSING OUTER LAYER MATERIAL: PVC80/R/BBER.
 11. ③ CABLE OUTER LAYER MATERIAL: PVC80H.
 12. ④ GROUND LINE.
 13. ⑤ GLASS BOARD THICKNESS: 4.



General Touch Technology Co., Ltd.
 No. 6, South Keqian Road, High-Tech Zone,
 Chengde City, Sichuan Province, P. R. China

DSN/DATE	CHK/DATE	APP/DATE	Scale
Touch Screen Drawing	TITLE: SCTTL4B22PIBR	dustproof touchscreen	1:1
Drawing No.:	Rev:	Sheet	1 of 1