

SB-3709

1x8 S-VIDEO • AUDIO DISTRIBUTION AMPLIFIER

Inputs : 1x S-VIDEO (Y/C), STEREO AUDIO (AR/AL)

Outputs : 8x S-VIDEO (Y/C), STEREO AUDIO (AR/AL)

DISTRIBUTOR

S-VIDEO AUDIO

SB-3709 1x8 DISTRIBUTION AMPLIFIER




SB-3709M 1RU 19inch Rack Metal case



Ear Rack : 1U-300L

SB-3709 S-VIDEO-AUDIO DISTRIBUTION AMPLIFIER 1x8



1x8 S-VIDEO-AUDIO DISTRIBUTION AMPLIFIER

SB-3709 is a 1 Input To 8 Outputs S-Video & Stereo Audio Distribution Amplifier. Video Bandwidth 440MHz Distribution Amplifier product. Its one of the most innovative S-Video(Y/C) and Stereo Audio (AR/AL) distribution amplifier product on the market Today. Support 19 inch Ear mount pair part number #1U-300L and MRM is 19 inch 1RU Rack mount type. It has 1 individual inputs with 8 individual outputs. Because it is a distributor, So the one input may be distribution to any 8 outputs in the same time. It completely eliminates the need to constantly move around S-Video and Stereo Audio input and output cables. This distribution amplifier is ideally suited for distributing S-Video/Audio signals from VCRs, Camcorders, Video Game Console, Video CDs, DVDs, Satellite Receivers, CATV Set-Top Box Devices to HD High Definition LCD Television for HDTV resolution 480p, 720p 1080i and 1080p or HD Plasma display monitor applications.

FEATURES

1. Support 1x8 Composite S-Video-Stereo Audio Distribution Amplifier
2. Distributing S-Video(Y/C) and Stereo Audio(AR/AL) Signals
3. Support HDTV Resolutions for 480i, 480p, 576p, 720p, 1080i and 1080p
4. S-Video Bandwidth : 440MHz (-3dB), 200 mVp-p
5. Audio bandwidth : 60MHz.
6. Audio Frequency Respond : 20Hz ~ 20KHz
7. Application Source devices from VCRs, Camcorders, Video Game Console, Video CDs, DVDs, Satellite Receivers, CATV Set-Top Box.
8. Suitable for distributing to HD high resolution Video player device and HDTV, LCD TV, Plasma TV, HD Monitor displays
9. Power switch control via selection pushbuttons with LED readout
10. Enclosure type : SB-3709M Support 19 inch Ear & 1RU Rack mountable
11. Support Lower power consumed full load under 480 mA
12. Power supply offer a universal type 100~230 VAC switch

SPECIFICATIONS

1. Type of distributor : 1 input to 8 outputs Distribution Amplifier
2. Type of Signals : S-Video(Y/C) via 1x RCA Female Connector
Stereo Audio (AR/AL) via 2x RCA Female Connectors
3. S-Video Bandwidth : 440MHz, (-3 dB) 2V p-p,
4. Audio Bandwidth : 60MHz, (-3dB) (Audio-Right=60MHz, Audio-Lift=60MHz)
5. Audio Frequency Respond : 20Hz ~ 20KHz
6. All Hostile Crosstalk : -56 db @ 5 MHz, -45 db @ 50 MHz
7. Scan Rates Accepted : 50Hz or 60Hz
8. Slew Rate : 1000V/us, Fixed internal gain of 2
9. Controls : Power switch selection via pushbuttons with LED readout
10. Safety Approvals : CE, FCC, RoHS(2002/95/EC)
11. Dimensions (W.D.H.) :
SB-3709 9.37" (304mm) x 5.95" (150mm) x 1.73" (44mm)
SB-3709M 17.32" (440mm) x 7.87" (200mm) x 1.73" (44mm)
12. Net Weight (Unit Only) : About 980 gwm (with metal case)
13. Power Voltage Input : DC 12V @0.66A