

KEY FEATURES

- Eight internal 6Gb/s SATA+SAS ports
- Two Mini-SAS internal connectors (SFF-8087)
- LSISAS2108 6Gb/s RAID-on-Chip
 800MHz PowerPC[®]
- 512MB 800MHz DDRII cache memory
- Optional battery backup module
- RAID Levels 0, 1, 5 and 6
- RAID Spans 10, 50 and 60

KEY ADVANTAGES

- Superior Performance
 Maximum Reads: 2,875MB/s
 Maximum Writes: 1,800MB/s
- PCI Express[®] 2.0 provides faster signaling for highbandwidth applications
- Support for 3Gb/s and 6Gb/s SATA and SAS hard drives
- SafeStore[™] Encryption Services for more secure data protection

TYPICAL APPLICATIONS

- Video-On-Demand
- Video-Surveillance
- Video Creation + Editing
- Medical Imaging
- High-Performance Computing
- Digital Content Archive and VTL
- Storage Appliance
- File, Web, Database, and Email Servers

MegaRAID[®] SAS 9260-8i / MegaRAID SAS 9260DE-8i Eight-Port 6Gb/s PCI Express SATA and SAS RAID Controller

Protect Business Critical Data with the Industry's Most Trusted SATA+SAS RAID Controllers

Next-Generation SATA+SAS RAID


LSI[™] MegaRAID SATA+SAS controllers provide a new level of reliability, availability, and performance to businesses that are facing storage challenges driven by unprecedented data growth. With data transfer rates of up to 6Gb/s per port, the MegaRAID SAS 9260-8i and 9260DE-8i bring users new features and improved performance, while continuing to support all the features of the previous 3Gb/s SATA+SAS generation. These two MegaRAID value line controllers, ideal for inside-thebox connectivity, employ the latest in RAID-on-Chip technology, comply with the PCI Express 2.0 specification, and provide additional data security using LSI SafeStore encryption services.

6Gb/s SAS Performance Advantage

6Gb/s SAS is designed for backward compatibility with 3Gb/s SAS as well as with 6Gb/s and 3Gb/s SATA hard drives. Regardless of the drive speed, 6Gb/s MegaRAID controllers will deliver significant performance improvements in both read and write applications as compared to their 3Gb/s predecessors. Other new features of the 6Gb/s MegaRAID SATA+SAS controllers include greater signal integrity using Decision Feedback Equalization, support for more sophisticated SAS topologies using Expander Self-discovery/ Self-configuration, and additional safeguards to enhance data protection.

LSI SafeStore Encryption Services

LSI is pleased to introduce SafeStore encryption services, which offer instant secure erase and local key management* for self-encrypting drives (SEDs). This technology represents a significant step forward in securing a drive's data from any unauthorized access or modification resulting from theft, loss, or repurposing of drives. Instant secure erase permanently removes data when repurposing or decommissioning SEDs. SafeStore local key management provides the necessary management and protection of SEDs using a simple pass phrase, security key identifier, and security key file, which can be set and applied to all SEDs assigned to a MegaRAID controller. This removes the complexity of managing each SED's unique encryption key, and essentially relieves the administrator from most of the daily tasks of securing data.



Intuitive RAID Management Utility

The MegaRAID Management Suite[™] provides the essential software tools to efficiently manage MegaRAID products, whether deployed in an enterprise or small business. LSI offers a collection of applications and tools including a pre-boot setup utility and a full spectrum of online RAID management utilities. This suite of applications allow administrators to adjust SAS topology views from the system host, controller and disk enclosure down to the logical and physical drive level. Extending to enterprise deployments, these tools scale to easily configure, monitor and manage RAID volumes locally or over the LAN network.

MEGARAID SAS 9260-81 AND MEGARAID SAS 9260DE-81

Solution Provided	Fight-port internal SATA+SAS solution for high-density ser	Eight-port internal SATA+SAS solution for high-density servers and workstations using up to 32 drives with the flexibility to use	
Solution Frontee	both SATA and SAS hard drives and solid state drives (SSDs)		
Physical Dimensions	MD2 Low profile (6.6" X 2.536")		
Connectors	Two Mini-SAS SFF-8087 internal connectors		
Device Support	Up to 32 SATA and/or SAS hard drives and SSDs		
Host Bus Type	x8 lane PCI Express 2.0 Compliant		
Data Transfer Rates	Up to 6Gb/s per port		
I/O Processor/SAS Controller	LSISAS2108 RAID-on-Chip (ROC)		
Cache Memory	512MB 800MHz DDR II SDRAM		
Battery Backup Unit	LSIiBBU07, an intelligent battery backup module option that directly connects to the controller		
Key RAID Data Protection Features	 RAID levels 0, 1, 5, and 6 RAID spans 10, 50 and 60 Online Capacity Expansion (OCE) Online RAID Level Migration (RLM) Auto resume after loss of system power during arrays array rebuild or reconstruction (RLM) Single controller Multipathing (failover) Load Balancing Configurable stripe size up to 1MB Fast initialization for quick array setup Check Consistency for background data integrity SafeStore™ Encryption Services Instant Secure Erase Local Key Management* SSD Support with SSD Guard™ 	 Patrol read for media scanning and repairing 64 logical drive support Up to 64TB LUN support DDF compliant Configuration on Disk (COD) S.M.A.R.T support Global and dedicated Hot Spare with Revertible Hot Spare support Automatic rebuild Enclosure affinity Emergency SATA hot spare for SAS arrays Enclosure management SGPIO (sideband) 	
Operating Temperature	Maximum ambient: 60°C (44.5°C w/iBBU)		
Operating Voltage	+3.3V		
Warranty	3 years, free advanced technical support, advanced replacement option		
Regulatory Certifications	EN55022, EN55024, EN60950, EN 61000-3-2, EN 61000-3-3; FCC Class A, Class B; UL1950; UL; CSA C22.2; VCCI; RRL for MIC; BSMI; C-tick		
RAID Management	MegaRAID Management Suite - MegaRAID Storage Manager™ - MegaCLI (command-line interface) - WebBIOS		
OS Support		Extensive support includes Microsoft® Windows® Vista/Server 2003/2000/XP, Linux® and more. Visit the LSI download Center for the most complete list of supported operating systems: lsi.com/support	

*local key management is supported only with the 9260DE-8i

For more information and sales office locations, please visit the LSI web sites at: lsi.com lsichannelgateway.com

LSI, LSI and Design logo, MegaRAID, SafeStore, SSD Guard, MegaRAID Management Suite, and MegaRAID Storage Manager are trademarks or registered trademarks of LSI Corporation. All other brand and product names may be trademarks of their respective companies.

LSI Corporation reserves the right to make changes to any products and services herein at any time without notice. LSI does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by LSI; nor does the purchase, lease, or use of a product or service from LSI convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual property rights of LSI or of third parties.

Copyright ©2009 by LSI Corporation. All rights reserved.

July 2009