

METAPACE

Metapace T-3 – Super priced fully equipped brand-name printer

www.metapace.com

Highlights

- Fully loaded direct thermal printer – at an entry-level price
- Prints receipts and tickets super quick with up to 200 mm/sec.
- Maximum paper width: 80 mm; max. resolution: 7 dots/mm (180 dpi)
- Integrated long-life auto cutter
- Flexible via modular interfaces: parallel, serial, USB 2.0 and Ethernet

Technical specifications

Print

Printing method	Direct thermal
Print speed	Max. 200 mm/s
Consumables	Thermal paper
Paper	Width: 79.5 mm +/- 0.5 mm, max. ø 83 mm
Print width	72 mm
Paper supply	Easy paper loading
Resolution	7 dots/mm (180 dpi)
Character sizes	Font A: 12x24, font B: 9x17, font C: 9x24
Bar codes	1D: EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, UPC-A, UPC-E, 2D: PDF417, QR Code

Electronics

Emulation	ESC/POS
Sensor	Paper Near End, Paper End, Cover Open
Memory	256 KBytes
Power Supply	AC 120 V ~ 230 V +/- 10%, DC 24 V, 2.3 A (included)
Reliability	150 km TPH, 1.8 million cuts, 70,000,000 lines

Specifics

Option	Wall mount bracket
--------	--------------------

Interfaces

I/F ports	RS232, parallel, USB 2.0, Ethernet (10/100 Base-T), 1x drawer kickout (RJ12)
-----------	--

Software

Operating system	2000/XP (32/64-bit) / 2003 Server (32/64-bit) / EPOS / VISTA, (32/64-bit) / 2008 Server (32/64-bit) / 7 (32/64-bit)
------------------	--

Housing

Dimensions (WxDxH)	148x200x150mm
Colour	Black

Warranty

Period	5 years
--------	---------

Direct Thermal
**RECEIPT
PRINTER**



T-3

METAPACE