

### Lightweight, Pocket-sized, Dependable



The Socket *Bluetooth* Cordless Hand Scanner (CHS) Series 7 brings industrial-class barcode scanning into a portable, pocket-sized form factor.

**Designed for Mobility:**

- Small, light, portable
- Wireless with long-range *Bluetooth* connection
- Excellent ergonomics ensure comfortable use over extended periods
- Dependable performance with long battery life
- Easy integration with applications on diverse mobile computing platforms



General Purpose  
(7Ci, 7M)



Extra Durable  
(7P)



General Purpose Barcode Scanners <i>Indoors</i>	7M	- For moderate to intensive scanning throughout 8-10 hour work shift - Class 2 laser has longer range for hard-to-reach areas like high shelves - Great for indoor scanning of ISBN or VIN (even scans through windshields)
Extra Durable Barcode Scanners <i>Indoors / Outdoors</i>	7P	- Efficiently scans thousands of barcodes per day, even on reflective surfaces - Best option for scanning VIN indoors and outdoors - even through windshield - High-performance Class 2 laser can read small or poorly printed barcodes
Apple Certified Barcode Scanner <i>Indoors</i>	7Ci	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> <p>Made for</p> </div> <ul style="list-style-type: none"> <li>- Smallest, lightest and most affordable version</li> <li>- For light-duty scanning (&lt;100 scans per day) up to 20" (51 cm) away</li> <li>- Scans barcodes printed on labels or displayed on device screens</li> <li>- Recommended for ISBN book scanning for book scouting or library apps</li> <li>- Contains authentication chip to allow <i>Bluetooth</i> SPP connections with Apple iOS devices (Requires latest SDK or compatible app)</li> <li>- Also supports Android, Windows, BlackBerry</li> </ul>

**HARDWARE FEATURES**

- Works with *Bluetooth* enabled PDAs, smartphones, tablets, notebooks and desktop computers:
  - Apple iPod touch, iPhone, iPad and Mac OS\*
  - Android OS
  - Windows Mobile, 7, Vista, XP
  - BlackBerry OS, QNX
- Class 1 *Bluetooth* 2.1 + EDR provides secure, long-range wireless connection up to 330 ft / 100 m
- Battery Friendly\* technology enables extensive battery life on a single charge
- Apple certified CHS 7Ci supports *Bluetooth* SPP connections with iPad, iPhone, iPod touch (Requires SDK or compatible app developed with SDK)<sup>1</sup>
- CHS 7P features extra durable exterior casing to withstand multiple 1.5 m (5 ft) drops to concrete
- Easy to use with automatic reconnections
- LED and beeps indicate good scan, connection, and power status
- Vibrate mode for good scans, great for noisy environments where beeps are hard to hear (7Ci and 7P only)
- Allows access to Apple iOS on-screen keyboard
- Supports *Bluetooth* HID connections for easy setup with no software installation<sup>2</sup>
- Supports *Bluetooth* SPP connections for advanced scanner control<sup>3</sup>

**SOFTWARE FEATURES (SPP mode only)**

- SocketScan™ 10 keyboard wedge software enters scanned data into any application — no custom programming needed
- Socket EZ Pair automates *Bluetooth* setup for maximum ease of use
- Suffix support — option to automatically add a carriage return or tab after each scan of data
- Configure beep, LED and vibrate settings
- Enable / disable symbology (barcode type)
- Monitor scanner battery level
- Determine the symbology or length of a barcode
- SocketScan 10 SDK available with optional developer compensation program <http://www.socketmobile.com/products/sdk/>

<sup>1</sup>CHS 7Ci supports *Bluetooth* SPP connections only with SocketScan 10 SDK v10.0.8 or later or compatible apps developed with the SDK. For a list of compatible apps, please visit: <http://www.socketmobile.com/appstore>

<sup>2</sup>HID not supported for BlackBerry OS or iPhone 3G.

<sup>3</sup>SPP not supported for Mac OS or QNX. SPP supported for iOS only with CHS 7Ci and SocketScan 10 SDK version 10.0.8 or later or a compatible apps developed with the SDK.

CHS Model	7Ci	7M (v3)	7P (v3)
SKU #	Scanner only: <b>CX2870-1409</b> With 10 hrs of SDK support & cradle: <b>SW1251-1464</b>	<b>CX2860-1296</b>	<b>CX2862-1298</b>
Dimensions	129 x 40.1 x 34.6 mm (5.07 x 1.57 x 1.36 in.)		132 x 45.1 x 37.9 mm (5.2 x 1.77 x 1.49 in.)
Total Mass	45 g (1.6 oz)	51 g (1.8 oz)	approx. 68 g (2.4 oz)
Type of Exterior Case	Standard exterior case withstands 1.2 m (4 ft) drops to vinyl-covered concrete		Extra durable, withstands 1.5 m (5 ft) drops to concrete
Optional Stylus Tip	Coming soon!	Included, designed for Pocket PC or other resistive device touch screens	
Temperature	Operating: +32 to +122°F (0 to +50°C) Storage: -22 to +158°F (-30 to +70°C) Ranges may vary with battery shelf life.		
Relative Humidity	5% to 95% non-condensing		
Ambient Light	Sunlight 9690 lux Artificial 4845 lux	Sunlight: 10,000 ft. candles (107,640 lux) Artificial light: 450 ft. candles (4,844 lux)	
Battery Type	Two AAA NiMH rechargeable batteries		
Battery Life	19 hours or 11,000 scans	19 hours or 15,000 scans <sup>1</sup>	
Battery Charging Time	With AC adapter: approx. 5 hours (under conditions of 0 to +40°C)		
Barcode Scanner Performance			
Scanner Type	Imager (1D)	Class 2 laser (1D)	Class 2 laser (1D)
Scans Barcodes on Device Screens	✓		
Scans VIN through windshield		✓	✓
Vibrate Mode for Good Scans	✓		✓
Symbologies Decoded	Same as 7M/P plus: UPC/EAN/JAN supplemental redundancy, Coupon Report, ISSN EAN, Inverse 1D, ISBT concatenations, Matrix 2 of 5	Bookland EAN (ISBN / EAN-13), Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN	
Scan Repetition Rate	50 scans/sec	100 scans/sec bi-directional	
Optical Resolution	5 mil minimum	0.004 inch (0.102 mm) min./barcode element width	
Print Contrast	Minimum 20%	Minimum 25% MRD at 650 nm	
Scan Angle	53.3° ± 3°	Wide (default): 47° ± 3° Narrow: 35° ± 3°	
Decode Distance <sup>2</sup>	5.7 to 50.8 cm (2.25 to 20 in.)	3.8 to 114+ cm (1.5 to 45+ inches)	
Bluetooth Profile Support	Human Interface Device (HID) and Serial Port Profile (SPP) Some OS versions or device models support only one profile.		
Bluetooth Protocol	Bluetooth 2.1 + EDR (Enhanced Data Rates) with 56 bit data encryption, Bluetooth QD ID B0164000		
Bluetooth Frequency	2.4 to 2.4835 GHz ISM band, supports Advanced Frequency Hopping		
Radio Range	Class 1 Bluetooth: Up to 330 ft (100 m), depending on environment		
OS Support	Please use online compatibility checker for specific device models, OS versions, etc. <a href="http://www.socketmobile.com/compatibilitychecker/">http://www.socketmobile.com/compatibilitychecker/</a>		
• Apple iOS: iPad, iPhone, iPod touch	✓	✓	✓
• Mac OS	✓	✓	✓
• Android OS	✓	✓	✓
• BlackBerry OS	✓	✓	✓
• Windows 7, Vista, XP, Mobile	✓	✓	✓
• QNX	✓	✓	✓
Apple iOS certified for iPad, iPhone, iPod touch	Certified. Has authentication chip to support Bluetooth SPP with iOS.	N/A - Works only in Bluetooth HID mode with Apple iOS devices	
SocketScan™ 10 Software	Keyboard wedge for Android, BlackBerry, Windows included. SDK sold separately <a href="http://www.socketmobile.com/products/sdk/">http://www.socketmobile.com/products/sdk/</a>		
Included Items	CHS barcode scanner, AAA rechargeable batteries (2), USB AC charger kit, Lanyard/belt clip with retractable tether, Software		
Warranty	Scanner: One year Accessories: 90 days		
SocketCare™ Service Program	Sold separately. SocketCare Plus 2 Year - SKU# SC1804-1349 SocketCare Plus 3 Year - SKU# SC1805-1350 <a href="http://www.socketcare.com/">http://www.socketcare.com/</a>		
Electrical Safety	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2		
Environmental	RoHS		
EMI / RFI	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELECOM		
Laser / LED Safety	IEC 60825-1, EN 60825-1		

<sup>1</sup>Based on elapse time of 5 seconds/scan under typical usage conditions. Battery performance may vary depending on vibrate settings and work environment.

<sup>2</sup>Depends on symbol size, symbology, label media, W-N ratio, scan angle.



[sales@socketmobile.com](mailto:sales@socketmobile.com)

Worldwide +1-510-933-3000  
Toll-Free +1-800-552-3300 (USA/Canada)

EMEA +33 682 719 381  
UK +44 (0) 7787 112109  
Asia Pacific +1 510 933 3122  
Latin America +1 510 933 3153