

PCR340 Dual Frequency RFID Reader for System Logon & Operator Identification

Introduction:

PCR340 is a simple- to- use device applying dual 125Khz and 13.56Mhz RFID technology to read the unique serial number of the RFID card. It is good to be used for the system access logon/logoff key and the system operator identification, such as POS system logon/logoff and operator identification /authorization with RFID card. PCR340 is a perfect system logon key which can protect the system and prevent the unauthorized people from using the system.

Features:

- Read either 125 Khz or 13.56Mhz frequency cards
- Designed with RS232 or PS/2 or USB interface
- Read unique serial number (UID) of the RFID card
- System Logon/Logoff
- Verify ID code for the system operator identification In addition to the ID code data, prefix or/and postfix characters can be set
- Cradle design to accept RFID card for the application as below:
- System is workable when the registered card is sitting on the cradle
- System is not workable when the registered card is removed from the cradle.

Applications:

- Systems security
- Personal Identification
- POS Systems
- Access Systems Logon/Logoff key
- Personal ID systems
- Automatic data logging

Specifications:

| Model | PCR340 | | |
|--------------------|---|-----|-----|
| Specification | | | |
| Interface | RS232 | PS2 | USB |
| Reading Frequency | 125Khz, 13.56Mhz | | |
| Baud rate | 19200 \ 14400 \ 9600 \ 4800 \ 2400 bps | | |
| Card types | EM compatible64 bits, ASK Manchester coding, ISO 14443A Mifare® MF1 1K&4K / Ultralight / DESFire; Read only (for unique serial number/ unique identifier) | | |
| Reading distance | 80 mm / 125KHz 40 mm / 13.56MHz | | |
| Power requirement | DC 5V, Stand by 70mA | | |
| Safety Certificate | CE / FCC | | |
| Dimensions | W120 x W86 x H42 mm | | |
| Environment | Operation Temperature: 0 ~ 50 Deg. C Storage Temperature: -10 ~ 60 Deg C Humidity: 10 ~ 90% | | |

Ordering information:

- PCR340 RS232 interface
- PCR340 PS2 interface
- PCR340 USB interface
- **※** Specification is subject to change without notice.





We welcome OEM inquiries

- ♦ Custom design manufacturing is available
- ♦ Custom device programming is available
- ♦ Call factory for other configuration



8F.,NO.31, LANE 169, KANG-NING STREET.HSI-CHIH.TAIPEI,TAIWAN TEL: 886-2-26954214 FAX: 886-2-26954213

e-mail: promag@gigatms.com.tw

http://www.gigatms.com.tw