

K-547

Standard layout with integrated touchpad.

- » Integrated capacitive touchpad
- » Versions:
 - 1) PS/2 + PS/2 version
 - 2) USB version



MAIN FEATURES

- » Compact keyboards with 101/102 or 104/105 OMRON B3F short-travel mechanical keyswitches
- » Long lifetime: more than 1 million operations
- » Actuating force: 2.55 N typically
- » Switch travel: 0.3 mm typically
- » PS/2 or USB standard communication protocols
- » Programmable keys with enable/disable function (USB interface only)
- » Support for the Protect function (USB versions only)
- » IP65 (from front side) protective membrane resistant to alcohol, diluted acids, diluted alkalis, esters, hydrocarbons, ketones and household cleaning agents
- » Different national layout membranes available (US English and German as standard)
- » Standard membrane colour: Pantone Warm Grey 2C
- » Standard MiniDIN6 or USB type A connector for keyboard connection
- » Standard PS/2 or USB pointing device (optional): trackball or touchpad
- » Desktop, panel and rack-mount versions
- » Operating temperature range: 0°C to + 40°C
- » Operating relative humidity range: <90% (non-condensing)
- » Storage temperature range: -10°C to + 50°C

PROTECTIVE MEMBRANE

- » Keyboards with short-travel switches are protected by a foil with the printed layout, which is glued on top of the metal mask. The foil is made of high-quality textured polyester film and embossed with a screen-printed polyester film. It is resistant to chemicals, abrasions and scratches and has a long flex life.

Foil properties:

- » Foil material: AUTOTEX® V150
- » Profile texture: velvet
- » Thickness: 150µm ± 10%
- » Switch life: 5×10⁶ flexes (typical)
- » Tensile strength: 160-250 MPa

KEYSWITCHES

Short-travel keyswitch

- » Type: OMRON B3F-4005
- » Key travel: 0.3^{+0.2}/_{-0.1} mm
- » Lifetime: 1×10⁶ operations (minimal)
- » Actuating force: 255 ± 69 cN

POINTING DEVICE

Touchpad

- » Type: Cirque TSM9920
- » Active area: 62.5 × 46.5 mm
- » Resolution: 40 counts/mm
- » Sample rate: 100 samples/s
- » Lifetime: 1×10⁷ strokes (500 km) (typical)

| | Power consumption: | Dimensions: | Packaging dimensions: | Package content: |
|-------|--------------------|-----------------------------|---------------------------|------------------|
| K-547 | 25 mATYP | 478,5 x 180 x 28 mm, 2260 g | 508 x 238 x 58 mm, 2410 g | keyboard |

