

# RACK AND PANEL VERSION

» K-LINE keyboards for integration in panel or rack.

# K-LINE

## K-647, K-847

Standard layout with integrated touchpad

- » Built-in 4H dimension
- » Fixing screws included for K-647
- » Fixing studs for K-847
- » Integrated capacitive touchpad
- » Versions:
  - 1) PS/2 + PS/2 version
  - 2) USB version



## MAIN FEATURES

- » Compact keyboards with 101/102 or 104/105 OMRON B3F short-travel mechanical keyswitches
- » Long lifetime: more than 1 million operations
- » Actuating force: 2.55 N typically
- » Switch travel: 0.3 mm typically
- » PS/2 or USB standard communication protocols
- » Programmable keys with enable/disable function (USB interface only)
- » Support for the Protect function (USB versions only)
- » IP65 (from front side) protective membrane resistant to alcohol, diluted acids, diluted alkalis, esters, hydrocarbons, ketones and household cleaning agents
- » Different national layout membranes available (US English and German as standard)
- » Standard membrane colour: Pantone Warm Grey 2C
- » Standard MiniDIN6 or USB type A connector for keyboard connection
- » Standard PS/2 or USB pointing device (optional): trackball or touchpad
- » Desktop, panel and rack-mount versions
- » Operating temperature range: 0°C to +40°C
- » Operating relative humidity range: <90% (non-condensing)
- » Storage temperature range: -10°C to +50°C

## PROTECTIVE MEMBRANE

» Keyboards with short-travel switches are protected by a foil with the printed layout, which is glued on top of the metal mask. The foil is made of high-quality textured polyester film and embossed with a screen-printed polyester film. It is resistant to chemicals, abrasions and scratches and has a long flex life.

Foil properties:

- » Foil material: AUTOTEX® V150
- » Profile texture: velvet
- » Thickness: 150µm ± 10%
- » Switch life: 5×10<sup>6</sup> flexes (typical)
- » Tensile strength: 160-250 MPa

## KEYSWITCHES

Short-travel keyswitch

- » Type: OMRON B3F-4005
- » Key travel: 0.3<sup>+0,2</sup>/<sub>-0,1</sub> mm
- » Lifetime: 1×10<sup>6</sup> operations (minimal)
- » Actuating force: 255 ± 69 cN

## POINTING DEVICE

Touchpad

- » Type: Cirque TSM9920
- » Active area: 62.5 × 46.5 mm
- » Resolution: 40 counts/mm
- » Sample rate: 100 samples/s
- » Lifetime: 1×10<sup>7</sup> strokes (500 km) (typical)

	Power consumption:	Dimensions:	Packaging dimensions:	Package content:
K-647	25 mATYP	482.6 x 177.8 x 42.5 mm, 1480 g	505 x 186 x 45 mm, 1665 g	keyboard, rack fixing bolts and nuts (4 pieces)
K-847	25 mATYP	482.6 x 177.8 x 42.5 mm, 1480 g	505 x 186 x 45 mm, 1665 g	keyboard

