

TKF-085b-TOUCH-MODUL



Modular Industrial Keyboards with integrated Pointing Device - Panel Versions

- Keyboard with different pointing devices available integrated solution
- Simple integration with studs on the reverse side
- Convenient, precise handling
- Frontside is fully sealed with touchpad
- Frontfoil with full-embossing for excellent tactile feedback
- Compact size layout, small footprint
- Various language versions available on request

Specification Keyboard:

Number of Keys: 85
 Keyswitch Technology: gold-on-gold-contact with metal domes
 Actuation Force/Travel: 2 N / 0.3 mm
 Keyswitch Lifetime: 1 Mio. operations
 Protection Level: IP65; NEMA 4x (frontside)
 Electronic Interfaces: PS/2; USB
 Connector: 6-pin MiniDIN; USB-A
 Dimensions: 365 x 135 x 20 mm 14.37" x 5.31" x 7,87"
 Operating Temperature: 0 °C to 50 °C
 Frontpanel Material: PCB-material, FR4

Specification Touchpad:

Motion Detection Method: capacitive
 Resolution: 40 counts / mm
 Protection Level: IP65; NEMA 4x (frontside)
 Electronic Interfaces: PS/2; USB
 Connector: 6-pin MiniDIN; USB-A
 Operating Temperature: 0 °C to 50 °C
 Frontpanel Material: PCB-material, FR4

Cat.-No.	Product Name
KF2031	TKF-085b-TOUCH-MODUL-PS/2 PS/2; US-Layout
KF2033	TKF-085b-TOUCH-MODUL-USB USB; US-Layout
Other language versions/interfaces/configuration available on request	

InduKey® Keyboard Production
 Mahnbrueck 4
 D-08233 Treuen
 Germany
 Phone: +49 / 37468 / 650 0
 Fax: +49 / 37468 / 650 50
 eMail: info@indukey.com
 Internet: www.indukey.com