



- NOTES**
1. ALL DIMENSION ARE IN MILLIMETERS.
  - ② TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN, GLASS IS BEVELED UNDER THE TRANSDUCERS.
  - ③ CABLE ROUTING ADDS A MAXIMUM OF 4.0mm TO INDICATED SECTION OF SCREEN.
  - ④ 8X19 HOUSING MATES WITH CONTROLLER.
  - ⑤ REFLECTONAL ARRAY AND ② TRANSDUCER ON THE FRONT OF THE GLASS.
  - ⑥ CABLE CLIP, MATERIAL: METAL.
  - ⑦ GLASS BOARD.
  - ⑧ CABLE, OUTER LAYER MATERIAL: PVCBG01.
  - 9 THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

|                     |  |
|---------------------|--|
| External Dimensions | 512*304*4  |
| Display Area        | 484*276  |
| Active Area         | 476*268  |
| Thickness           | 4  |
| Anti-Glare          | Y <input type="checkbox"/> N <input checked="" type="checkbox"/> |
| DustPro             | Y <input type="checkbox"/> N <input checked="" type="checkbox"/> |
| WaterPro            | Y <input type="checkbox"/> N <input checked="" type="checkbox"/> |
| Safety              | Y <input type="checkbox"/> N <input checked="" type="checkbox"/> |

CONNECTION CHART

| PIN | SIGNAL | INSULATION COLOR OVERALL SHIELD |
|-----|--------|---------------------------------|
| 1   | GND    |                                 |
| 2   | KEY    |                                 |
| 3   | Y-in2  | BLUE                            |
| 4   | Yout   | BLUE                            |
| 5   | Y-in1  | BLACK                           |
| 6   | GND    | YELLOW                          |
| 7   | GND    |                                 |
| 8   | X-in2  | GREEN                           |
| 9   | X-in1  | WHITE                           |
| 10  | Xout   | RED                             |
| 11  | X-in1  | RED                             |
| 12  | KEY    |                                 |

